

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product

AC ADAPTER

Name and address of the applicant

Shenzhen Xin Ju Kang Technology Co., Ltd
4/F., Bldg D, Liuxian 2 Rd., Area 71, Xinan Street, Bao'an District
Shenzhen, Guangdong 518101 CHINA

Name and address of the manufacturer

Shenzhen Xin Ju Kang Technology Co., Ltd
4/F., Bldg D, Liuxian 2 Rd., Area 71, Xinan Street, Bao'an District
Shenzhen, Guangdong 518101 CHINA

Name and address of the factory

Note: When more than one factory, please report on page 2

Shenzhen Kezhen Electronic Co., Ltd
4/F., Bldg D, Liuxian 2 Rd., Area 71, Xinan Street, Bao'an District
Shenzhen, Guangdong 518101
CHINA Additional Information on page 2

Ratings and principal characteristics

Input: 100-240V~, 50/60Hz, 0.6A max
Output: 5-24Vdc, 0.01-4.5A

None

Trademark (if any)

Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

KZxxxxxyyz
See Page 2

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to EN 60950-1:2006 /A11:2009 /A1:2010
/A12:2011 /A2:2013; National Differences specified in the CB
Test Report. Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1, IEC 60950-1(ed.2);am2

As shown in the Test Report Ref. No. which forms part of this Certificate

SA1707145S 001 issued on 2017-09-28

This CB Test Certificate is issued by the National Certification Body



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2017-11-08

Signature:

Jan-Erik Storgaard



Ref. Certif. No.

DK-67967-UL

Model Details:

KZxxxxyyyz ("xxx"=050-240 indicate output voltage range from 5.0V-24.0V, minimum step by 0.1V and "yyy"=0010-4500 indicate output current range from 0.01A-4.5A, minimum step by 0.01A; z= V, B, U, J, A, C, D, K, E, T, denotes different plug type for different countries.)

Additional information (if necessary)



- UL (US), 333 Pflingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2017-11-08

Signature:

Jan-Erik Storgaard