

EN 50663: 2017
EN 62479: 2010
ASSESSMENT REPORT

For
Shenzhen Sonoff Technologies Co.,Ltd.

1001, BLDG8, Lianhua Industrial Park, shenzhen, GD, China

Tested Model: DW2-RF

| | |
|--|---|
| Report Type: Original Report | Product Type: RF Wireless Door/Window Sensor |
| Report Number: | RDG200109006 |
| Report Date: | 2020-06-01 |
| Reviewed By: | Dean Lau RF Supervisor |
| Test Laboratory: | Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn |

TABLE OF CONTENTS

| | |
|--|----------|
| GENERAL INFORMATION | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3 |
| OBJECTIVE | 3 |
| TEST METHODOLOGY | 3 |
| DECLARATIONS..... | 4 |
| RF EXPOSURE MEASUREMENT | 5 |
| EN 62479:2010 §4.1 & §4.2 - MAXIMUM EMITTED AVERAGE POWER | 8 |
| TEST PROCEDURE | 8 |
| TEST DATA | 8 |
| EXHIBIT A – EUT PHOTOGRAPHS | 9 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

| | |
|-----------------------------|--------------------------------|
| EUT Name: | RF Wireless Door/Window Sensor |
| EUT Model: | DW2-RF |
| Rated Input Voltage: | DC 12V From battery |
| Serial Number: | RDG200109006-RF-S1 |
| EUT Received Date: | 2020.05.22 |
| EUT Received status: | Good |

Objective

This report is prepared on behalf of **Shenzhen Sonoff Technologies Co.,Ltd.** in accordance with EN 62479: 2010 Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz); and EN 50663: 2017 Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz).

The objective is to determine the compliance of EUT with EN 62479: 2010 and EN 50663: 2017.

Test Methodology

All measurements contained in this report were conducted with EN 62479: 2010 and EN 50663: 2017.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “ Δ ”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

RF Exposure Measurement

1. Introduction

This generic standard applies to low power electronic and electrical apparatus for which no dedicated product – or product family standard regarding human exposure to electromagnetic fields applies.

The frequency range covered is 10 MHz to 300 GHz.

The object of this standard is to demonstrate the compliance of such apparatus with the basic restrictions on exposure of the general public to electric, magnetic and electromagnetic fields and contact current.

2. Compliance Criteria

2.1 General considerations

Compliance of electromagnetic emissions from electronic and electrical equipment with the basic restrictions usually is determined by measurements and, in some cases, calculation of the exposure level. If the electrical power used by or radiated by the equipment is sufficiently low, the electromagnetic fields emitted will be incapable of producing exposures that exceed the basic restrictions. This standard provides simple EMF assessment procedures for this low power equipment.

Any relevant compliance assessment procedure which is consistent with the state of the art, reproducible and gives valid results can be used.

For transmitters intended for use with more than one antenna configuration option, the combination of transmitter and antenna(s) which generates the highest available antenna power and/or average total radiated power shall be assessed.

Four routes, which as described as follows, can be used to demonstrate compliance with this standard:

A Typical usage, installation and the physical characteristics of equipment make it inherently compliant with the applicable EMF exposure levels such as those listed in the bibliography. This low-power equipment includes unintentional (or non-intentional) radiators, for example incandescent light bulbs and audio/visual (A/V) equipment, information technology equipment (ITE) and multimedia equipment (MME) that does not contain radio transmitters. NOTE Equipment is described as A/V equipment, ITE or MME if its main use is playback/recording of music, voice or images, or processing of digital information.

B The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in 2.2.

C The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in 2.2.

D Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in 2.2.

If none of these routes can be used, then the equipment is deemed to be out of the scope of this standard and EMF assessment for conformity assessment purposes shall be made according to other standards, such as IEC 62311 or other EMF product standards.

2.2 Low-power exclusion level (P_{max})

Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level P_{max}.

Annex A contains example values for P_{max} derived from existing exposure limits listed in the bibliography, such as the ICNIRP guidelines [1], IEEE Std C95.1-1999 [2], and IEEE Std C95.1-2005 [3].

For wireless devices operated close to a person's body with available antenna powers and/or average total radiated powers higher than the P_{max} values given in Annex A, the alternative P_{max} values (called P_{max}'), described in Annex B can also be used.

For low power equipment using pulsed signals, other limits may apply in addition to those considered in Annex A and Annex B. Both ICNIRP guidelines [1] and IEEE standards [2], [3] have specific restrictions on exposures to pulsed fields, and the requirements of those standards with respect to exposure to pulses shall be met. Annex C discusses this topic further.

2.3 Exposure to multiple transmitting sources

If equipment under test (EUT) is equipped with multiple intentional radiators, the overall conformity assessment might require more than just the assessment of conformity of each one of the radiators separately. The effect of multiple intentional radiators should be considered in the conformity assessment process.

Technical Report IEC 62630 [8] provides generic guidance on how to assess the EMFs generated by multiple intentional radiators.

3. Limit

3.1 Annex A

Table A.1 – Example values of SAR-based P_{max} for some cases described by ICNIRP, IEEE Std C95.1-1999 and IEEE Std C95.1-2005

| Guideline / Standard | SAR limit, S _{A,R} _{max} W/kg | Averaging mass, m g | P _{max} mW | Exposure tier ^a | Region of body ^a |
|-------------------------|--|------------------------|------------------------|----------------------------|------------------------------------|
| ICNIRP [1] | 2 | 10 | 20 | General public | Head and trunk |
| | 4 | 10 | 40 | General public | Limbs |
| | 10 | 10 | 100 | Occupational | Head and trunk |
| | 20 | 10 | 200 | Occupational | Limbs |
| IEEE Std C95.1-1999 [2] | 1,6 | 1 | 1,6 | Uncontrolled environment | Head, trunk, arms, legs |
| | 4 | 10 | 40 | Uncontrolled environment | Hands, wrists, feet and ankles |
| | 8 | 1 | 8 | Controlled environment | Head, trunk, arms, legs |
| | 20 | 10 | 200 | Controlled environment | Hands, wrists, feet and ankles |
| IEEE Std C95.1-2005 [3] | 2 | 10 | 20 | Action level | Body except extremities and pinnae |
| | 4 | 10 | 40 | Action level | Extremities and pinnae |
| | 10 | 10 | 100 | Controlled environment | Body except extremities and pinnae |
| | 20 | 10 | 200 | Controlled environment | Extremities and pinnae |

^a Consult the appropriate standard for more information and definitions of terms.

3.2 Annex B

Table B.1 – Some typical frequency bands of portable wireless devices and corresponding low-power exclusion levels P_{max}' predicted using Equations (B.1) through (B.9)

| f GHz | BW % | Example air interface | P_{max}' mW | | | |
|------------|---------|--------------------------|--------------------|--------------------|---------------------|--------------------|
| | | | $s = 5 \text{ mm}$ | | $s = 25 \text{ mm}$ | |
| | | | $m = 1 \text{ g}$ | $m = 10 \text{ g}$ | $m = 1 \text{ g}$ | $m = 10 \text{ g}$ |
| 0,393 | 3,8 | TETRA | 97 | 292 | 265 | 526 |
| 0,420 | 4,8 | TETRA | 98 | 293 | 274 | 541 |
| 0,461 | 3,3 | GSM | 80 | 244 | 233 | 468 |
| 0,485 | 14,4 | APCO | 117 | 337 | 347 | 660 |
| 0,838 | 7,6 | IDEN | 48 | 148 | 198 | 399 |
| 0,859 | 8,1 | IS-136 | 47 | 145 | 198 | 398 |
| 0,884 | 16,7 | PDC | 54 | 162 | 233 | 456 |
| 0,896 | 5,7 | TETRA | 40 | 127 | 176 | 360 |
| 0,918 | 4,8 | IDEN | 37 | 118 | 165 | 342 |
| 0,925 | 7,6 | GSM | 41 | 129 | 185 | 375 |
| 1,465 | 4,9 | PDC | 17 | 60 | 128 | 281 |
| 1,795 | 9,5 | GSM | 13 | 50 | 139 | 308 |
| 1,920 | 7,3 | GSM | 11 | 44 | 132 | 302 |
| 2,045 | 12,2 | UMTS | 11 | 44 | 146 | 330 |
| 2,350 | 4,3 | WiBro | 7,9 | 34 | 130 | 323 |
| 2,442 | 3,4 | 802.11b | 7,3 | 32 | 130 | 328 |
| 3,550 | 14,1 | WiMAX | 6,7 | 37 | 244 | 657 |
| 5,250 | 3,8 | WiMAX | 6,8 | 53 | 258 | 845 |
| 5,788 | 1,3 | WiMAX | 6,2 | 52 | 164 | 564 |

EN 62479:2010 §4.1 & §4.2 - MAXIMUM EMITTED AVERAGE POWER**Test Procedure**

Refer to EN 62479:2010 §4.1 & §4.2 and EN 50663:2017 §6.

Test Data

| Mode | Frequency Band(MHz) | Tune-up conducted power | | Limit (mW) | Result |
|------|---------------------|-------------------------|-------|------------|--------|
| | | dBm | mW | | |
| SRD | 433.92 | -28 | 0.002 | 20 | Pass |

Conclusion:

No SAR test required.

EXHIBIT A – EUT PHOTOGRAPHS

For photos in this section, please refer to report No.: RDG200109006-02 EXHIBIT A.

*******END OF REPORT*******