



Test Report



中国认可
国际互认
检测
TESTING
CNAS L6964

Report No. : UNIB21071220LR-01

Page 1 / 19

Applicant : Shenzhen Sonoff Technologies Co.,Ltd.

Address : 1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

Name of sample : Wi-Fi Smart LED RGB Light Strip

Receiving Date : Jul. 12, 2021

Test Date : Jul. 15, 2021

Test Address : No.47-3, Industrial Road, Zhushan, Dalong Street, Panyu District, Guangzhou, Guangdong, China

Test Method : EN 62471:2008 Photobiological safety of lamps and lamp systems

Testing Item : See the conclusion item

Decision Basis : EN 62471:2008 Photobiological safety of lamps and lamp systems

Conclusion : Pass

Signed for and on behalf of
Shenzhen United Testing Technology Co.,Ltd

Liuze
Approved Signatory

Aug. 25, 2021

Issue Date

1、 Sample information

For samples, the information provided by the customer is as follows:

Product Name : Wi-Fi Smart LED RGB Light Strip
 Trade Mark : N/A
 Main Model : 5050RGB Lite-5M
 Rting(S) : DC4.5V
 Manufacturer : Shenzhen Sonoff Technologies Co.,Ltd.
 Manufacturer Address : 1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

2、 Conclusion

The sample was detected and according to the detection results, the conclusion are as follows:

Test item	Decision Basis	Conclusion
Actinic UV, Es	EN 62471:2008 Photobiological safety of lamps and lamp systems	Pass
Near UV, Euva		Pass
Blue light, Lb		Pass
Retinal thermal, Lr		Pass
Retinal thermal, weak visual stimulus, Lir		Pass
IR radiation,eye, Eir		Pass

3、Test item particulars

Test item particulars	
Test item Description	: Wi-Fi Smart LED RGB Light Strip
Trademark	: N/A
Model and/or type reference	: 5050RGB Lite-5M
Rating(s)	: DC4.5V
Test item particulars	
Lamp Type	: LED Lamp
Emission Condition	: <input checked="" type="checkbox"/> Continuous wave emission <input type="checkbox"/> Pulse emission
Possible test case verdicts	
- test case does not apply to the test object	: N/A
- test object does meet the requirement	: P (Pass)
- test object does not meet the requirement	: F (Fail)
Lamp classification group	: <input checked="" type="checkbox"/> Exempt <input type="checkbox"/> Risk 1 <input type="checkbox"/> Risk 2 <input type="checkbox"/> Risk 3
General remarks:	
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report.	
Throughout this report a <input type="checkbox"/> comma / <input checked="" type="checkbox"/> point is used as the decimal separator.	
Summary of testing: The test samples are complying with the relevant product standard(s) and all applicable test clauses. -EN 62471:2008	

Ambient temperature for test	: 25.3°C 50RH
Test input voltage	: 220.0V
Current	: 0.275A
Power	: 27.18W
Power factor	: 0.450

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict
4	EXPOSURE LIMITS		P
4.1	General		P
	The exposure limits in this standard is not less than 0,01 ms and not more than any 8-hour period and should be used as guides in the control of exposure		P
	Detailed spectral data of a light source are generally required only if the luminance of the source exceeds $10^4 \text{ cd}\cdot\text{m}^{-2}$	see clause 4.3	P
4.3	Hazard exposure limits		P
4.3.1	Actinic UV hazard exposure limit for the skin and eye		P
	The exposure limit for effective radiant exposure is $30 \text{ J}\cdot\text{m}^{-2}$ within any 8-hour period		P
	To protect against injury of the eye or skin from ultraviolet radiation exposure produced by a broadband source, the effective integrated spectral irradiance, E_s , of the light source shall not exceed the levels defined by:		P
	$E_s \cdot t = \sum_{200}^{400} \sum_t E_\lambda(\lambda, t) \cdot S_{UV}(\lambda) \cdot \Delta t \cdot \Delta \lambda \leq 30 \quad \text{J}\cdot\text{m}^{-2}$		P
	The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye or skin shall be computed by:		P
	$t_{\max} = \frac{30}{E_s} \quad \text{s}$		P
4.3.2	Near-UV hazard exposure limit for eye		P
	For the spectral region 315 nm to 400 nm (UV-A) the total radiant exposure to the eye shall not exceed $10000 \text{ J}\cdot\text{m}^{-2}$ for exposure times less than 1000 s. For exposure times greater than 1000 s (approximately 16 minutes) the UV-A irradiance for the unprotected eye, E_{UVA} , shall not exceed $10 \text{ W}\cdot\text{m}^{-2}$.		P
	The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye for time less than 1000 s, shall be computed by:		N/A
	$t_{\max} \leq \frac{10\,000}{E_{UVA}} \quad \text{s}$		N/A
4.3.3	Retinal blue light hazard exposure limit		P

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

SZ: 2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang Community, Xixiang Str, Bao'an District, Shenzhen, China.

深圳市宝安区西乡街道铁岗社区宝田一路365号嘉皇源科技园附楼2楼(P.C.518102) Tel:+86-755-86180996 Fax:+86-755-86180156

GZ: #47-3, Industrial Road, Zhushan Village, Dalong Street, Panyu District, Guangzhou, China.

广州市番禺区大龙街竹山村工业路 47-3 (P.C. 511450) Tel:+86-20-3927769 Fax:+86-755-86180156

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict
	To protect against retinal photochemical injury from chronic blue-light exposure, the integrated spectral radiance of the light source weighted against the blue-light hazard function, $B(\lambda)$, i.e., the blue-light weighted radiance, L_B , shall not exceed the levels defined by:		P
	$L_B \cdot t = \sum_{300}^{700} \sum_t L_\lambda(\lambda, t) \cdot B(\lambda) \cdot \Delta t \cdot \Delta \lambda \leq 10^6 \quad \text{J} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	for $t \leq 10^4 \text{ s}$ $t_{\max} = \frac{10^6}{L_B}$	N/A
	$L_B = \sum_{300}^{700} L_\lambda \cdot B(\lambda) \cdot \Delta \lambda \leq 100 \quad \text{W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	for $t > 10^4 \text{ s}$	P
4.3.4	Retinal blue light hazard exposure limit - small source		N/A
	Thus the spectral irradiance at the eye E_λ , weighted against the blue-light hazard function $B(\lambda)$ shall not exceed the levels defined by:		N/A
	$E_B \cdot t = \sum_{300}^{700} \sum_t E_\lambda(\lambda, t) \cdot B(\lambda) \cdot \Delta t \cdot \Delta \lambda \leq 100 \quad \text{J} \cdot \text{m}^{-2}$		N/A
	$E_B = \sum_{300}^{700} E_\lambda \cdot B(\lambda) \cdot \Delta \lambda \leq 1 \quad \text{W} \cdot \text{m}^{-2}$		N/A
4.3.5	Retinal thermal hazard exposure limit		P
	To protect against retinal thermal injury, the integrated spectral radiance of the light source, L_λ , weighted by the burn hazard weighting function $R(\lambda)$ (from Figure 4.2 and Table 4.2), i.e., the burn hazard weighted radiance, shall not exceed the levels defined by:		P
	$L_R = \sum_{380}^{1400} L_\lambda \cdot R(\lambda) \cdot \Delta \lambda \leq \frac{50\,000}{\alpha \cdot t^{0,25}} \quad \text{W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	($10 \mu\text{s} \leq t \leq 10 \text{ s}$)	P
4.3.6	Retinal thermal hazard exposure limit – weak visual stimulus		P
	For an infrared heat lamp or any near-infrared source where a weak visual stimulus is inadequate to activate the aversion response, the near infrared (780 nm to 1400 nm) radiance, L_{IR} , as viewed by the eye for exposure times greater than 10 s shall be limited to:		P
	$L_{IR} = \sum_{780}^{1400} L_\lambda \cdot R(\lambda) \cdot \Delta \lambda \leq \frac{6\,000}{\alpha} \quad \text{W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	$t > 10 \text{ s}$	P

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict
4.3.7	Infrared radiation hazard exposure limits for the eye		P
	The avoid thermal injury of the cornea and possible delayed effects upon the lens of the eye (cataractogenesis), ocular exposure to infrared radiation, E_{IR} , over the wavelength range 780 nm To 3000 nm, for times less than 1000 s, shall not exceed:		P
	$E_{IR} = \sum_{780}^{3000} E_{\lambda} \cdot \Delta\lambda \leq 18000 \cdot t^{-0.75} \quad W \cdot m^{-2}$	$t \leq 1000 \text{ s}$	N/A
	For times greater than 1000 s the limit becomes		P
	$E_{IR} = \sum_{780}^{3000} E_{\lambda} \cdot \Delta\lambda \leq 100 \quad W \cdot m^{-2}$	$t > 1000 \text{ s}$	P
4.3.8	Thermal hazard exposure limit for the skin		P
	Visible and infrared radiant exposure (380 nm to 3000 nm) of the skin shall be limited to:		P
	$E_H \cdot t = \sum_{380}^{3000} \sum_t E_{\lambda}(\lambda, t) \cdot \Delta t \cdot \Delta\lambda \leq 20000 \cdot t^{0.25} \quad J \cdot m^{-2}$		P

5	MEASUREMENT OF LAMPS AND LAMP SYSTEMS		P
5.1	Measurement conditions		P
	Measurement conditions shall be reported as part of the evaluation against the exposure limits and the assignment of risk classification.		P
5.1.1	Lamp ageing (seasoning)		P
	Seasoning of lamps shall be done as stated in the appropriate IEC lamp standard.		P
5.1.2	Test environment		P
	For specific test conditions, see the appropriate IEC lamp standard or in absence of such standards, the appropriate national standards or manufacturer's recommendations.		P
5.1.3	Extraneous radiation		P
	Careful checks should be made to ensure that extraneous sources of radiation and reflections do not add significantly to the measurement results.		P

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict
5.1.4	Lamp operation		P
	Operation of the test lamp shall be provided in accordance with:		P
	– the appropriate IEC lamp standard, or		P
	– the manufacturer's recommendation		P
5.1.5	Lamp system operation		N/A
	The power source for operation of the test lamp shall be provided in accordance with:		N/A
	– the appropriate IEC standard, or		N/A
	– the manufacturer's recommendation		N/A
5.2	Measurement procedure		P
5.2.1	Irradiance measurements		P
	Minimum aperture diameter 7mm.		P
	Maximum aperture diameter 50 mm.		P
	The measurement shall be made in that position of the beam giving the maximum reading.		P
	The measurement instrument is adequate calibrated.		P
5.2.2	Radiance measurements		P
5.2.2.2	Alternative method		N/A
	Alternatively to an imaging radiance set-up, an irradiance measurement set-up with a circular field stop placed at the source can be used to perform radiance measurements.		N/A
5.2.3	Measurement of source size		P
	The determination of α , the angle subtended by a source, requires the determination of the 50% emission points of the source.		P
5.2.4	Pulse width measurement for pulsed sources		N/A
	The determination of Δt , the nominal pulse duration of a source, requires the determination of the time during which the emission is > 50% of its peak value.		N/A

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict
5.3	Analysis methods		P
5.3.1	Weighting curve interpolations		P
	To standardize interpolated values, use linear interpolation on the log of given values to obtain intermediate points at the wavelength intervals desired.	see table 4.1	P
5.3.2	Calculations		P
	The calculation of source hazard values shall be performed by weighting the spectral scan by the appropriate function and calculating the total weighted energy.		P
5.3.3	Measurement uncertainty		P
	The quality of all measurement results must be quantified by an analysis of the uncertainty.	see Annex C in the norm	P

6	LAMP CLASSIFICATION		P
	For the purposes of this standard it was decided that the values shall be reported as follows:	see table 6.1	P
	– for lamps intended for general lighting service, the hazard values shall be reported as either irradiance or radiance values at a distance which produces an illuminance of 500 lx, but not at a distance less than 200 mm	500lx	P
	– for all other light sources, including pulsed lamp sources, the hazard values shall be reported at a distance of 200 mm		N/A
6.1	Continuous wave lamps		P
6.1.1	Except Group		P
	In the except group are lamps, which does not pose any photobiological hazard. The requirement is met by any lamp that does not pose:		P
	– an actinic ultraviolet hazard (Es) within 8-hours exposure (30000 s), nor		P

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

SZ: 2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang Community, Xixiang Str, Bao'an District, Shenzhen, China.

深圳市宝安区西乡街道铁岗社区宝田一路365号嘉皇源科技园附楼2楼(P.C.518102) Tel:+86-755-86180996 Fax:+86-755-86180156

GZ: #47-3, Industrial Road, Zhushan Village, Dalong Street, Panyu District, Guangzhou, China.

广州市番禺区大龙街竹山村工业路47-3 (P.C. 511450) Tel:+86-20-39277769 Fax:+86-755-86180156

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict
	– a near-UV hazard (E_{UVA}) within 1000 s, (about 16 min), nor		P
	– a retinal blue-light hazard (L_B) within 10000 s (about 2,8 h), nor		P
	– a retinal thermal hazard (L_R) within 10 s, nor		P
	– an infrared radiation hazard for the eye (E_{IR}) within 1000 s		P
6.1.2	Risk Group 1 (Low-Risk)		N/A
	In this group are lamps, which exceeds the limits for the except group but that does not pose:		N/A
	– an actinic ultraviolet hazard (E_S) within 10000 s, nor		N/A
	– a near ultraviolet hazard (E_{UVA}) within 300 s, nor		N/A
	– a retinal blue-light hazard (L_B) within 100 s, nor		N/A
	– a retinal thermal hazard (L_R) within 10 s, nor		N/A
	– an infrared radiation hazard for the eye (E_{IR}) within 100 s		N/A
	Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard (L_{IR}), within 100 s are in Risk Group 1.		N/A
6.1.3	Risk Group 2 (Moderate-Risk)		N/A
	This requirement is met by any lamp that exceeds the limits for Risk Group 1, but that does not pose:		N/A
	– an actinic ultraviolet hazard (E_S) within 1000 s exposure, nor		N/A
	– a near ultraviolet hazard (E_{UVA}) within 100 s, nor		N/A
	– a retinal blue-light hazard (L_B) within 0,25 s (aversion response), nor		N/A
	– a retinal thermal hazard (L_R) within 0,25 s (aversion response), nor		N/A
	– an infrared radiation hazard for the eye (E_{IR}) within 10 s		N/A

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict
	Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard (L_{IR}), within 10 s are in Risk Group 2.		N/A
6.1.4	Risk Group 3 (High-Risk)		N/A
	Lamps which exceed the limits for Risk Group 2 are in Group 3.		N/A
6.2	Pulsed lamps		N/A
	Pulse lamp criteria shall apply to a single pulse and to any group of pulses within 0,25 s.		N/A
	A pulsed lamp shall be evaluated at the highest nominal energy loading as specified by the manufacturer.		N/A
	The risk group determination of the lamp being tested shall be made as follows:		N/A
	– a lamp that exceeds the exposure limit shall be classified as belonging to Risk Group 3 (High-Risk)		N/A
	– for single pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance does is below the EL shall be classified as belonging to the Exempt Group		N/A
	– for repetitively pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance dose is below the EL, shall be evaluated using the continuous wave risk criteria discussed in clause 6.1, using time averaged values of the pulsed emission		N/A

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict

Table 4.1 Spectral weighting function for assessing ultraviolet hazards for skin and eye			P
Wavelength ¹ λ , nm	UV hazard function $S_{UV}(\lambda)$	Wavelength λ , nm	UV hazard function $S_{UV}(\lambda)$
200	0,030	313*	0,006
205	0,051	315	0,003
210	0,075	316	0,0024
215	0,095	317	0,0020
220	0,120	318	0,0016
225	0,150	319	0,0012
230	0,190	320	0,0010
235	0,240	322	0,00067
240	0,300	323	0,00054
245	0,360	325	0,00050
250	0,430	328	0,00044
254*	0,500	330	0,00041
255	0,520	333*	0,00037
260	0,650	335	0,00034
265	0,810	340	0,00028
270	1,000	345	0,00024
275	0,960	350	0,00020
280*	0,880	355	0,00016
285	0,770	360	0,00013
290	0,640	365*	0,00011
295	0,540	370	0,000093
297*	0,460	375	0,000077
300	0,300	380	0,000064
303*	0,120	385	0,000053
305	0,060	390	0,000044
308	0,026	395	0,000036
310	0,015	400	0,000030

¹ Wavelengths chosen are representative: other values should be obtained by logarithmic interpolation intermediate wavelengths.

* Emission lines of a mercury discharge spectrum.

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict

Table 4.2 Spectral weighting functions for assessing retinal hazards from broadband optical sources			P
Wavelength nm	Blue-light hazard function B (λ)	Burn hazard function R (λ)	
300	0,01		
305	0,01		
310	0,01		
315	0,01		
320	0,01		
325	0,01		
330	0,01		
335	0,01		
340	0,01		
345	0,01		
350	0,01		
355	0,01		
360	0,01		
365	0,01		
370	0,01		
375	0,01		
380	0,01	0,1	
385	0,013	0,13	
390	0,025	0,25	
395	0,05	0,5	
400	0,10	1,0	
405	0,20	2,0	
410	0,40	4,0	
415	0,80	8,0	
420	0,90	9,0	
425	0,95	9,5	
430	0,98	9,8	
435	1,00	10,0	

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict

Table 4.2 Spectral weighting functions for assessing retinal hazards from broadband optical sources			P
Wavelength nm	Blue-light hazard function B (λ)	Burn hazard function R (λ)	
440	1,00	10,0	
445	0,97	9,7	
450	0,94	9,4	
455	0,90	9,0	
460	0,80	8,0	
465	0,70	7,0	
470	0,62	6,2	
475	0,55	5,5	
480	0,45	4,5	
485	0,40	4,0	
490	0,22	2,2	
495	0,16	1,6	
500-600	$10^{[(450-\lambda)/50]}$	1,0	
600-700	0,001	1,0	
700-1050		$10^{[(700-\lambda)/500]}$	
1050-1150		0,2	
1150-1200		$0,2 \cdot 10^{0,02(1150-\lambda)}$	
1200-1400		0,02	

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict

Table 5.4 Summary of the ELs for the surface of the skin or cornea (irradiance based values)					P
Hazard Name	Relevant equation	Wavelength range nm	Exposure duration sec	Limiting aperture rad (deg)	EL in terms of constant irradiance $W \cdot m^{-2}$
Actinic UV skin & eye	$E_S = \sum E_\lambda \cdot S(\lambda) \cdot \Delta\lambda$	200 – 400	< 30000	1,4 (80)	30/t
Eye UV-A	$E_{UVA} = \sum E_\lambda \cdot \Delta\lambda$	315 – 400	≤ 1000 >1000	1,4 (80)	10000/t 10
Blue-light small source	$E_B = \sum E_\lambda \cdot B(\lambda) \cdot \Delta\lambda$	300 – 700	≤ 100 >100	< 0,011	100/t 1,0
Eye IR	$E_{IR} = \sum E_\lambda \cdot \Delta\lambda$	780 – 3000	≤ 1000 >1000	1,4 (80)	18000/t ^{0,75} 100
Skin thermal	$E_H = \sum E_\lambda \cdot \Delta\lambda$	380 – 3000	< 10	2π sr	20000/t ^{0,75}

Table 5.5 Summary of the ELs for the retina (radiance based values)					P
Hazard Name	Relevant equation	Wavelength range nm	Exposure duration sec	Field of view radians	EL in terms of constant radiance $W \cdot m^{-2} \cdot sr^{-1}$
Blue light	$L_B = \sum L_\lambda \cdot B(\lambda) \cdot \Delta\lambda$	300 – 700	0,25 – 10 10-100 100-10000 ≥ 10000	$0,011 \cdot \sqrt{(t/10)}$ 0,011 $0,0011 \cdot \sqrt{t}$ 0,1	$10^6/t$ $10^6/t$ $10^6/t$ 100
Retinal thermal	$L_R = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$	380 – 1400	< 0,25 0,25 – 10	0,0017 $0,011 \cdot \sqrt{(t/10)}$	$50000/(\alpha \cdot t^{0,25})$ $50000/(\alpha \cdot t^{0,25})$
Retinal thermal (weak visual stimulus)	$L_{IR} = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$	780 – 1400	> 10	0,011	6000/α

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.



Test Report

Report No. : UNIB21071220LR-01

Page 15 / 19

EN 62471			
Clause	Requirement Test	Result-Remark	Verdict

Table 6.1		Emission limits for risk groups of continuous wave lamps of Red light						P	
Risk	Action spectrum	Symbol	Units	Emission Measurement					
				Exempt		Low risk		Mod risk	
				Limit	Result	Limit	Result	Limit	Result
Actinic UV	SUV(λ)	E _S	W•m ⁻²	0,001	0.000E+00	0,003	--	0,03	--
Near UV		E _{UVA}	W•m ⁻²	0.33	0.000E+00	33	--	100	--
Blue light	B(λ)	L _B	W•m ⁻² •sr ⁻¹	100	1.391E-02	10000	--	4000000	--
Blue light, small source	B(λ)	E _B	W•m ⁻²	1,0*	--	1,0	--	400	--
Retinal thermal	R(λ)	L _R	W•m ⁻² •sr ⁻¹	28000/ α	5.247E+01	28000/ α	--	71000/ α	--
Retinal thermal, weak visual stimulus**	R(λ)	L _{IR}	W•m ⁻² •sr ⁻¹	6000/ α	0.000E+00	6000/ α	--	6000/ α	--
IR radiation, eye	---	E _{IR}	W•m ⁻²	100	6.375E-06	570	--	3200	--

* Small source defined as one with $\alpha < 0,011$ radian. Averaging field of view at 10000 s is 0,1 radian.
 ** Involves evaluation of non-GLS source
 Note: Angular subtense of apparent source: 70.14 mrad

Table 6.1				Emission limits for risk groups of continuous wave lamps of Blue light				P	
Risk	Action spectrum	Symbol	Units	Emission Measurement					
				Exempt		Low risk		Mod risk	
				Limit	Result	Limit	Result	Limit	Result
Actinic UV	SUV(λ)	E _S	W•m ⁻²	0,001	1.496E-07	0,003	--	0,03	--
Near UV		E _{UVA}	W•m ⁻²	0.33	1.578E-03	33	--	100	--
Blue light	B(λ)	L _B	W•m ⁻² •sr ⁻¹	100	2.584E+01	10000	--	4000000	--
Blue light, small source	B(λ)	E _B	W•m ⁻²	1,0*	--	1,0	--	400	--
Retinal thermal	R(λ)	L _R	W•m ⁻² •sr ⁻¹	28000/ α	1.189E+03	28000/ α	--	71000/ α	--
Retinal thermal, weak visual stimulus**	R(λ)	L _{IR}	W•m ⁻² •sr ⁻¹	6000/ α	0.000E+00	6000/ α	--	6000/ α	--
IR radiation, eye	---	E _{IR}	W•m ⁻²	100	0.000E+00	570	--	3200	--

* Small source defined as one with $\alpha < 0,011$ radian. Averaging field of view at 10000 s is 0,1 radian.
 ** Involves evaluation of non-GLS source
 Note:Angular subtense of apparent source:71.24mrad

Table 6.1				Emission limits for risk groups of continuous wave lamps of White light				P	
Risk	Action spectrum	Symbol	Units	Emission Measurement					
				Exempt		Low risk		Mod risk	
				Limit	Result	Limit	Result	Limit	Result
Actinic UV	SUV(λ)	E _S	W•m ⁻²	0,001	1.581E-07	0,003	--	0,03	--
Near UV		E _{UVA}	W•m ⁻²	0.33	2.109E-03	33	--	100	--
Blue light	B(λ)	L _B	W•m ⁻² •sr ⁻¹	100	1.653E+01	10000	--	4000000	--
Blue light, small source	B(λ)	E _B	W•m ⁻²	1,0*	--	1,0	--	400	--
Retinal thermal	R(λ)	L _R	W•m ⁻² •sr ⁻¹	28000/ α	7.133E+02	28000/ α	--	71000/ α	--
Retinal thermal, weak visual stimulus**	R(λ)	L _{IR}	W•m ⁻² •sr ⁻¹	6000/ α	0.000E+00	6000/ α	--	6000/ α	--
IR radiation, eye	---	E _{IR}	W•m ⁻²	100	1.956E-02	570	--	3200	--

* Small source defined as one with $\alpha < 0,011$ radian. Averaging field of view at 10000 s is 0,1 radian.
 ** Involves evaluation of non-GLS source
 Note:Angular subtense of apparent source:66.43 mrad

List of test equipment used:

Manufacturer	Description	Equipment ID	Model	Last Calibration date	Calibration due date
SENSING	Measuring System for Assessment of Optical Radiation safety	LC01	SPR-5000	2020-11-02	2021-11-02

Sample Photo



5050RGB Lite-5M



5050RGB Lite-5M

The sample picture is only used to inform the customer that the sample received by the laboratory is shown in the picture, which does not prove the appearance and quality of the customer's products.

*****End of Report*****

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.
SZ: 2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang Community, Xixiang Str, Bao'an District, Shenzhen, China.
深圳市宝安区西乡街道铁岗社区宝田一路365号嘉皇源科技园附楼2楼(P.C.518102) Tel:+86-755-86180996 Fax:+86-755-86180156
GZ: #47-3, Industrial Road, Zhushan Village, Dalong Street, Panyu District, Guangzhou, China.
广州市番禺区大龙街竹山村工业路 47-3 (P.C. 511450) Tel:+86-20-39277769 Fax:+86-755-86180156

声明/ Statement

1、本报告必须有授权签字人签名和报告专用章，否则视为报告无效，若 PDF 格式的报告中若无本实验室的防伪电子章或显示为“X”，报告无效。

This report must have the signature of the authorized signatory and the special seal of the report, otherwise it will be considered invalid, If there is no anti-counterfeiting electronic seal of the laboratory in the report in PDF format or it is displayed as "X", the report is invalid.

2、本报告不得擅自修改、增加和删除。

This report shall not be modified, added or deleted without authorization.

3、本报告的结果只对委托方提供给本实验室检验检测的样品（无特殊说明，指报告“Sample Photo(s)”中所呈现的样品）有效。

The results of this report are only valid for the samples provided by Applicant to our laboratory for inspection (without special explanation, it refers to the samples presented in the report "Sample Photo(s)").

4、若对本报告的测试数据和结论有异议，请在报告签发日期后 10 个工作日内以书面形式提出，逾期不予受理。

If there is any objection to the test data and conclusions of this report, please submit it in writing within 10 working days after the date of issuance of the report.

5、未经本公司书面同意，不得复制本报告（全文复制除外），亦不可作为宣传品或者广告使用。

Without the written consent of the company, this report shall not be copied (except for full copy), nor shall it be used as publicity materials or advertising.

6、报告封面仅作装饰用，不在报告正文内。

The cover of the report is for decoration only, not included in the body of the report.

7、本公司出具的纸质报告与电子版报告具备相同的效力，当两者内容有差异时，以电子版报告为准。

The paper report issued by our company has the same effect as the electronic report. In case of any difference between the two, the electronic report shall prevail.

8、本公司出具的中文和英文的报告具备相同的效力，当理解出现差异时，以中文为准。

The Chinese and English reports issued by our company have the same effect. In case of any difference in understanding, the Chinese version shall prevail.

9、查询报告时请提供本公司出具的完整的报告文档。

Please provide the complete report documents issued by our company when inquiring the report.

10、对于需要根据测试值做符合性判定的情况，相关的规范、标准、文件和客户无相关要求且无特殊说明时，本实验室出具的检验检测报告采用全数值进行且采用 ILAC-G8:09/2019 中“Simple Acceptance Rule（简单接受规则）”进行判定。

For cases where compliance is determined based on test values, when relevant specifications, standards, documents, and customers have no relevant requirements and no other special instructions, the test report issued by this laboratory is carried out in full value and adopts ILAC-G8:09 /2019 "Simple Acceptance Rule" for judgment.

11、在中华人民共和国境内，本报告无CMA认可状态标识时，报告仅供科研、教学或内部质量控制等活动使用。

In the People's Republic of China, when there is no CMA Accredited Symbol in this report, the report is only for scientific research, teaching or internal quality control activities.

This document cannot be reproduced except in full, without the prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. To check the authenticity of testing report, please contact us.

SZ: 2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang Community, Xixiang Str, Bao'an District, Shenzhen, China.

深圳市宝安区西乡街道铁岗社区宝田一路365号嘉皇源科技园附楼2楼(P.C.518102) Tel:+86-755-86180996 Fax:+86-755-86180156

GZ: #47-3, Industrial Road, Zhushan Village, Dalong Street, Panyu District, Guangzhou, China.

广州市番禺区大龙街竹山村工业路 47-3 (P.C. 511450) Tel:+86-20-3927769 Fax:+86-755-86180156