

EN IEC 62311:2020

ASSESSMENT REPORT

For

Shenzhen Sonoff Technologies Co.,Ltd.

1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

Tested Model: RF BridgeR2

Report Type: Original Report	Product Type: RF BridgeR2
Report Number:	<u>RDG210222005</u>
Report Date:	<u>2021-03-31</u>
Reviewed By:	Gavin Xu RF Engineer
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE.....	3
TEST METHODOLOGY.....	3
DECLARATIONS.....	4
TECHNICAL REQUIREMENTS SPECIFICATION IN EN IEC 62311.....	5
TEST DATA.....	6
EXHIBIT A - EUT PHOTOGRAPHS	7

F I N A L

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	RF BridgeR2
EUT Model:	RF BridgeR2
Rated Input Voltage:	DC 5V from adapter
Serial Number:	RDG210222005-RF-S1
EUT Received Date:	2021.02.23
EUT Received Status:	Good

Objective

This report is prepared on behalf of *Shenzhen Sonoff Technologies Co.,Ltd.* in accordance with EN IEC 62311:2020, Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz to 300 GHz)

The objective is to determine the compliance of EUT with EN IEC 62311:2020.

Test Methodology

All measurements contained in this report were conducted with EN IEC 62311:2020.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A 2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Technical Requirements Specification in EN IEC 62311

General Description of Applied Standards

In general, the basic restrictions shall be used as exposure limits for the assessment of compliance. However, in most cases reference levels are used as limits. Such reference levels for exposure to electric, magnetic and electromagnetic fields are derived from the basic restrictions using realistic worst-case assumptions about exposure. If the reference levels are met, then the basic restrictions will also be met; if the reference levels are exceeded, that does not necessarily mean that the basic restrictions are exceeded. In some situations, it may be possible to show compliance with the basic restrictions directly. It may also be possible to derive compliance criteria that allow a simple measurement or calculation to demonstrate compliance with the basic restrictions. Often these compliance criteria can be derived using realistic assumptions about conditions under which exposures from a device may occur, rather than the conservative assumptions that are the basis for the reference levels.

RF Exposure Evaluation

Limit:

According to EN IEC 62311, the criteria listed in the below table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified table 2 of Council Recommendation 1999/519/EC.

Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field(μ T)	Equivalent plane wave power density $S_{eq}(W/m^2)$
0-1 Hz	-	$3,2 \times 10^4$	4×10^4	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	$4\ 000/f$	$5\ 000/f$	-
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	-
0,8-3 kHz	$250/f$	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	$0,73/f$	$0,92/f$	-
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Notes:

- f as indicated in the frequency range column.

Test method

The antenna of the product, under normal use condition is at least 20cm away from the body of the user. So, this product under normal use is located on electromagnetic far field between the human body.

Far Field Calculation Formula

$$E = \frac{\sqrt{30PG(\theta, \phi)}}{r}$$

G= antenna gain relative to an isotropic antenna
 θ, φ= elevation and azimuth angles to point of investigation
 r= distance from observation point to the antenna

Test Data

Mode	Tune-up EIRP/ERP	E-field Strength	Limit
	(dBm)	(V/m)	(V/m)
2.4G Wi-Fi	16	5.46	61
SRD	-8	0.34	28.64

Note: The distance from observation point to the antenna is 20cm.

Conclusion: Compliance

EXHIBIT A - EUT PHOTOGRAPHS

For photos in this section, please refer to report No.: RDG210222005-02 EXHIBIT A.

*******END OF REPORT*******