

# Shenzhen Sonoff Technologies Co., Ltd.

# CE TEST REPORT

**SCOPE OF WORK:**

EMF report

**Model:**

B02-BL-A60/B02-B-A60/B02-A60, L02-BL-A60/L02-B-A60/L02-A60

**REPORT NUMBER**

220100633HZH-005

**ISSUE DATE**

February 22, 2022

**DOCUMENT CONTROL NUMBER**

TTRF62311\_V2  
© 2020 Intertek



**Applicant** : Shenzhen Sonoff Technologies Co., Ltd.  
1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

**Manufacturer** : Shenzhen Sonoff Technologies Co., Ltd.  
1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

**Manufacturing site** : Hengdian Group Tospo Lighting Co., Ltd.  
Hengdian Industrial Zone, Dongyang City, Zhejiang Province,  
P.R.China

## Summary

The equipment complies with the requirements according to the following standard(s) or Specification:

**1999/519/EC:** COUNCIL RECOMMENDATION of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)

**EN IEC 62311:2020:** Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)

PREPARED BY:

REVIEWED BY:

Offa Zhou  
Project Engineer



Wakeyou Wang  
Reviewer



This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Revision History**

<b>Report No.</b>	<b>Version</b>	<b>Description</b>	<b>Issued Date</b>
220100633HZH-005	Rev. 01	Initial issue of report	February 22, 2022

**TEST REPORT**

**1.1 Measurement Uncertainty**

Item No.	Assessment Items	Relative uncertainty
1	Power density	22%
Note: the assessed relative uncertainty is less than the permissible maximum uncertainty (30%), and therefore the calculated value shall be compared directly with the applicable limit for the evaluation of compliance.		

### Appendix I

According to assessment method & relevant limit showed in Appendix III of this report, the MPE limit for the frequency higher than 2GHz is 10W/m<sup>2</sup> (namely 1mW/cm<sup>2</sup>).

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm<sup>2</sup>

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

We can see from the test reports LCS210819074AEB and LCS210819074AEC:

Mode	Frequency Bands (MHz)	P (dBm)	P (mW)	R (cm)	S (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11b	2472	15.46	35.2	20	0.007	1

Mode	Frequency Bands (MHz)	P (dBm)	P (mW)	R (cm)	S (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
BLE	2402	1.47	1.4	20	0.0003	1

The wifi function and BLE function can be simultaneous transmission, so the maximum total power density (S) is 0.007/1+0.0003/1 <1.

Conclusion: This device complies with health requirements of 2014/53/EU as well as Radio Equipment Regulations 2017.

## Appendix II

**Definition below must be outlined in the User Manual:**

To satisfy RF exposure requirements, a separation distance of **20 cm** or more should be maintained between this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended. The antenna used for this transmitter must not be co-located in conjunction with any other antenna or transmitter.

**Appendix III**

**Assessment methods & Limit for Electromagnetic Exposure Evaluation**

**Assessment methods:**

- Far field calculation
- Near field calculation
- Simulation with/without a phantom
- Numerical modeling
- Body/limb current
- SAR
- E and H measurement
- Source modeling
- Direct measurement of physical properties: Contact current

**Reference levels for electric, magnetic and electromagnetic fields (Table 2 of 1999/519/EC)**

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	4 000/f	5 000/f	-
0,025-0,8 kHz	250/f	4/f	5/f	-
0,8-3 kHz	250/f	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	0,73/f	0,92/f	-
1-10 MHz	$87/f^{1/2}$	0,73/f	0,92/f	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	f/200
2-300 GHz	61	0,16	0,20	10

**Notes:**

1. *f* as indicated in the frequency range column.
2. For frequencies between 100 kHz and 10 GHz,  $S_{eq}$ ,  $E^2$ ,  $H^2$ , and  $B^2$  are to be averaged over any six-minute period.
3. For frequencies exceeding 10 GHz,  $S_{eq}$ ,  $E^2$ ,  $H^2$ , and  $B^2$  are to be averaged over any  $68/f^{1.05}$  - minute period (*f* in GHz).
4. No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.
5. The shading grid stands for the applied limit in this report.

\*\*\*\*\* END \*\*\*\*\*