

EN IEC 62311:2020

ASSESSMENT REPORT

For

Shenzhen Sonoff Technologies Co., Ltd.

1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

Tested Model: NSPanel-US

Report Type: Amended Report	Product Type: NSPanel Smart Scene Wall Switch
Report Number:	DG1220712-31540EA1
Report Date:	2022-07-16
Reviewed By:	Rocky Xiao RF Engineer
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
DECLARATIONS.....	3
EXHIBITB – EUT PHOTOGRAPHS	4
BELOW IS THE ORIGINAL REPORT	5

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	DG1210804-32577E	Original Report	2021-08-31
1	DG1220712-31540EA1	Amended Report	2022-07-16

Note: This is the amended report application which was based on the original report. The differences between them as following:

1. Reduce the size of the product shell(control part), without change the circuit (Please refer to EUT photos).

The change between the previous equipment and the current equipment is stated and guaranteed by the applicant. The difference between them will not affect the test results, we will keep the test results, test photos, but update the related EUT photos.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol“▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

EXHIBITB – EUT PHOTOGRAPHS

For photos in this section, please refer to report No.: DG1220712-31540E-02A1 EXHIBIT A.

BELOW IS THE ORIGINAL REPORT

EN IEC 62311:2020

ASSESSMENT REPORT

For

Shenzhen Sonoff Technologies Co., Ltd.

1001, BLDG8, Lianhua Industrial Park, Shenzhen, GD, China

Tested Model: NSPanel-US


Report Type: Original Report	Product Type: NSPanel Smart Scene Wall Switch
Report Number:	DG1210804-32577E
Report Date:	2021-08-31
Reviewed By:	Rocky Xiao RF Engineer 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE	3
TEST METHODOLOGY	3
DECLARATIONS.....	3
TECHNICAL REQUIREMENTS SPECIFICATION IN EN 62311.....	4
TEST DATA	5
EXHIBIT A – EUT PHOTOGRAPHS.....	6

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Name:	NSPanel Smart Scene Wall Switch
Test Model:	NSPanel-US
Rated Input Voltage:	100-240Vac 50/60Hz
Serial Number:	DG1210804-32577E-RF-S2
EUT Received Date:	2021.08.04
EUT Received Status:	Good

Objective

This report is prepared on behalf of *Shenzhen Sonoff Technologies Co., Ltd.* in accordance with EN IEC 62311:2020, Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz to 300 GHz).

The objective is to determine the compliance of EUT with EN IEC 62311:2020.

Test Methodology

All measurements contained in this report were conducted with EN IEC 62311:2020.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Technical Requirements Specification in EN 62311

General Description of Applied Standards

In general, the basic restrictions shall be used as exposure limits for the assessment of compliance. However, in most cases reference levels are used as limits. Such reference levels for exposure to electric, magnetic and electromagnetic fields are derived from the basic restrictions using realistic worst-case assumptions about exposure. If the reference levels are met, then the basic restrictions will also be met; if the reference levels are exceeded, that does not necessarily mean that the basic restrictions are exceeded. In some situations, it may be possible to show compliance with the basic restrictions directly. It may also be possible to derive compliance criteria that allow a simple measurement or calculation to demonstrate compliance with the basic restrictions. Often these compliance criteria can be derived using realistic assumptions about conditions under which exposures from a device may occur, rather than the conservative assumptions that are the basis for the reference levels.

RF Exposure Evaluation

Limit:

According to EN 62311, the criteria listed in the below table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified table 2 of Council Recommendation 1999/519/EC.

Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field(μ T)	Equivalent plane wave power density $S_{eq}(W/m^2)$
0-1 Hz	-	$3,2 \times 10^4$	4×10^4	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	4 000/f	5 000/f	-
0,025-0,8 kHz	250/f	4/f	5/f	-
0,8-3 kHz	250/f	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	0,73/f	0,92/f	-
1-10 MHz	$87/f^{1/2}$	0,73/f	0,92/f	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	f/200
2-300 GHz	61	0,16	0,20	10

Notes:

1. f as indicated in the frequency range column.

Test method

Far Field

The antenna of the product, under normal use condition is at least 20cm away from the body of the user. So, this product under normal use is located on electromagnetic far field between the human body.

Far Field Calculation Formula

$$E = \frac{\sqrt{30PG(\theta, \phi)}}{r}$$

Where:

P= Tune-up average conducted power

G= antenna gain relative to an isotropic antenna

θ, ϕ = elevation and azimuth angles to point of investigation

r= distance from observation point to the antenna

Test Data

RF Mode	Tune-up EIRP		E-Field Strength	Limit	Result
	(dBm)	(mW)	(V/m)	(V/m)	
Wi-Fi	15	31.63	4.87	61	Pass
BLE	3	2	1.22	61	Pass

Note: The distance from observation point to the antenna is 20cm.

Conclusion: Compliance

EXHIBIT A – EUT PHOTOGRAPHS

For photos in this section, please refer to report No.: DG1210804-32577E-02 EXHIBIT A.

*******END OF REPORT*******